

I.D. (mm)	Weights (1) (2) - (kg/piece)									
	O.D. (mm)									
	100	105	110	115	120	125	130	135	140	150
35	17.70	19.60	21.35	23.85	-	-	-	-	-	-
40	17.10	18.95	20.75	23.25	25.20	28.30	30.65	-	-	-
45	16.40	18.30	20.05	22.55	24.50	27.60	29.95	32.10	34.65	41.35
50	15.65	17.50	19.25	21.80	23.75	26.85	29.20	31.35	33.85	40.55
55	14.75	16.60	18.40	20.95	22.90	25.95	28.35	30.45	33.00	39.70
60	13.80	15.65	17.45	20.00	21.95	25.00	27.40	29.50	32.05	38.75
65	12.75	14.60	16.35	18.95	20.90	24.00	26.35	28.50	31.00	37.70
70	11.60	13.45	15.20	17.80	19.75	22.85	25.20	27.35	29.90	36.60
75	10.35	12.20	14.00	16.60	18.55	21.65	24.00	26.10	28.65	35.35
80	9.01	10.85	12.65	15.30	17.20	20.30	22.70	24.80	27.35	34.05
85	7.59	9.45	11.25	13.90	15.80	18.90	21.30	23.40	25.95	32.65
90	-	7.94	9.73	12.40	14.35	17.45	19.80	21.90	24.45	31.15
95	-	-	8.13	10.80	12.75	15.85	18.20	20.35	22.85	29.60
100	-	-	-	9.13	11.10	14.15	16.55	18.65	21.20	27.90
105	-	-	-	-	9.31	12.40	14.80	16.90	19.45	26.15
110	-	-	-	-	-	10.55	12.95	15.05	17.60	24.30
115	-	-	-	-	-	-	11.00	13.10	15.65	22.35
120	-	-	-	-	-	-	-	11.10	13.60	20.30
125	-	-	-	-	-	-	-	-	11.50	18.20
130	-	-	-	-	-	-	-	-	-	16.00
135	-	-	-	-	-	-	-	-	-	13.70
Standard length (mm): 2000 (0 + 60) - (3)										
(*) : for product codes and tolerances on the diameters: see page 27.										