

| Thicknesses (mm) | Tolerances (1) on the thicknesses (mm) | Weights (2) - (kg/m) | |
|--------------------------|-------------------------------------------|------------------------------------------|-----------|
| | | natural | black |
| | | 40004004 | 40004104 |
| 8 | + 0.2 +0.9 | 6.15 | D 6.15 |
| 10 | | 7.59 | D 7.59 |
| 12 | + 0.3 +1.5 | 9.28 | D 9.28 |
| 15 | | 11.45 | D 11.45 |
| 16 | | 12.15 | D 12.15 |
| 20 | | 15.05 | D 15.05 |
| 25 | | 18.65 | D 18.65 |
| 30 | + 0.5 +2.5 | 22.65 | D 22.65 |
| 35 | | 26.25 | D 26.25 |
| 40 | | 29.85 | D 29.85 |
| 45 | | 33.45 | [] 33.45 |
| 50 | | 37.05 | D 37.05 |
| 60 | + 0.5 +3.5 | 44.60 | D 44.60 |
| 70 | | D 51 .80 | D 51.80 |
| 80 | + 0.5 +5 | D 59.55 | D 59.55 |
| 90 | | 0 66.75 | D 66.75 |
| 100 | | D 73.95 | D 73.95 |
| Standard sizes (mm) | | Tolerances (1) on width and lengths | |
| 610x1000 610x3000 | | Width : + 5 mm + 25 mm Lengths : 0 + 3 % | |
| Cut-to-size products : D | | | |