

Diameters (mm)	Tolerances (1) on the diameters (mm)	Weights (2) - (kg/m)	
		natural	black
		40000000	40000100
5	+ 0.1 +0.4	• 0.025	0.025
6		• 0.035	o 0.035
8	+ 0.1 +0.5	• 0.063	0.063
10		• 0.096	• 0.096
12	+ 0.2 +0.7	• 0.141	• 0.141
14		• 0.190	0.190
15		• 0.217	0.217
16		• 0.246	• 0.246
18		• 0.309	0 0.309
20		• 0.380	• 0.380
22		+ 0.2 +0.9	• 0.462
25	• 0.595		• 0.595
28	• 0.740		0.740
30	• 0.850		• 0.850
32	+ 0.2 +1.1	• 0.970	• 0.970
36		• 1.22	• 1.22
40		• 1.50	• 1.50
45	+ 0.3 +1.3	• 1.91	• 1.91
50		• 2.35	• 2.35
56		• 2.93	• 2.93
60	+ 0.3 +1.6	• 3.38	• 3.38
65		• 3.95	3.95
70		• 4.57	• 4.57
75	+ 0.4 +2	• 5.28	5.28
80		• 5.99	• 5.99
85	+ 0.5 +2.2	• 6.78	6.78
90		• 7.58	• 7.58
95	+ 0.6 +2.5	• 8.47	8.47
100		• 9.37	• 9.37
110	+ 0.7 +3	• 11.35	11.35
120	+ 0.8 + 3.5	• 13.55	• 13.55
125		• 14.70	• 14.70
130	+ 0.9 +3.8	• 15.90	• 15.90
140		• 18.40	18.40
150	+ 1 +4.2	• 21.15	• 21.15
160	+ 1.1 +4.5	• 24.10	24.10
170	+ 1.2 +5	• 27.25	27.25
180		• 30.45	• 30.45
190	+ 1.3 +5.5	• 34.00	34.00
200		• 37.60	• 37.60

220	+ 1.3 +5.8	• 45.40	45.40
250	+ 1.5 +6.2	• 58.55	58.55
280	+ 1.6 +6.5	• 73.30	73.30
300	+ 1.7 +7	• 84.20	84.20
320	+ 1.8 +7.4	• 95.75	95.75
Standard lengths (mm)		Tolerance (1) on the lengths (%)	
1000 3000		0 +3	
Non-standard lengths (cut-to-size) :			